

<b>Subject:</b>	Safety Data Sheet – Nickel Cadmium Battery				
<b>Document No:</b>	GYSUK 029	<b>Revision:</b>	B	<b>Date:</b>	7 <sup>th</sup> July 2020

**OPENING STATMENT**

According to REACH regulation (EC1907/2006, Article 31) these batteries are considered to be ARTICLES with no intended release.

RoHS- Directive 2011/65/EU refers batteries to 2006/66EC and in turn to 2002/95/EC. The 2002/95/EC directive does not apply to batteries used in electrical and electronic equipment.

Once batteries are removed from 'end of life' electrical and electronic equipment batteries should comply again with the Battery directive 2011/65/EU as waste batteries. It is a requirement under this directive that all batteries should be recycled at end-of-life.

**SECTION I – SUPPLIERS INFORMATION**

GS Yuasa Battery Sales UK Ltd.  
 Unit 13, Hunts Rise,  
 South Marston Park,  
 Swindon.  
 Wiltshire.  
 SN3 4TG  
 Telephone number for information 01793 833555

**SECTION II – HAZARDOUS INGREDIENTS**

**IMPORTANT NOTE:**

The battery should not be opened or burned. Exposure to the ingredients within or their combustion products could be harmful.

INGREDIENTS INFORMATION		
Ingredients name	CAS No.	% W. t.
Nickel di-hydroxide	12054-48-7	19.2
Cobalt oxide	1307-96-6	2.5
Nickel power	7440-02-0	0.9
Cadmium oxide	1306-19-0	28.3
Cadmium	7440-43-9	3.3
Potassium hydroxide	1310-58-3	3.7
Nickel	7440-02-0	5
Iron	7439-89-6	34.4
Vinylon	N/A	2.7

<b>Subject:</b>	Safety Data Sheet – Nickel Cadmium Battery				
<b>Document No:</b>	GYSUK 029	<b>Revision:</b>	B	<b>Date:</b>	7 <sup>th</sup> July 2020

**Remark:**

The NiCad battery is neither substance nor mixture but a finished article. It has no risk to life and health under normal use or transportation. Ingredients of the battery do not leak out by virtue of the hermetical sealing with metal case.

The electrolyte is corrosive. Contact with internal components may cause irritation or severe burns; irritating to eyes, respiratory system and skin.

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

Boiling Point:	NA	Specific Gravity (H2O=1):	NA
Vapour Pressure (mm Hg):	NA	Melting Point:	NA
Vapour Density (AIR=1):	NA	Evaporation Rate (Butyl Acetate):	NA
Solubility in Water:	NA	Appearance and Odour:	Cylindrical shape, odourless

**SECTION IV - REACTIVITY DATA**

Stability	Unstable	Conditions to Avoid
	Stable X	
Hazardous Polymerization	May Occur	Conditions to Avoid
	Will Not Occur X	
Incompatibility (Materials to Avoid)		
Hazardous Decomposition or By products		

**SECTION V - FIRE AND EXPLOSION HAZARD DATA**

If fire or explosion occurs when batteries are on charge shut off power to charger.

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing materials. Cool exterior of batteries if exposed to fire to prevent rupture.

<b>Subject:</b>	Safety Data Sheet – Nickel Cadmium Battery				
<b>Document No:</b>	GYSUK 029	<b>Revision:</b>	B	<b>Date:</b>	7 <sup>th</sup> July 2020

Fire fighters should wear self-contained breathing apparatus. Nickel-Cadmium batteries involved in a fire can vent and produce toxic fumes including nickel, nickel oxide, cadmium, cadmium oxides, and cobalt oxides.

## SECTION VI - HEALTH HAZARD DATA

Under normal conditions the battery is hermetically sealed.

### Ingestion:

Swallowing a battery can be harmful.

Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. Contents include toxic cadmium compounds that can cause excessive salivation, choking, nausea, persistent vomiting, diarrhea, abdominal pain, dizziness, faintness, unconsciousness, and possible liver and kidney injury.

If a battery or open battery is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately

### Inhalation:

Contents of an open battery can cause respiratory irritation. Cadmium oxide fumes can cause metal fume fever. Hypersensitivity to nickel can cause allergic pulmonary asthma. Provide fresh air and seek medical attention.

### Skin Contact:

Contents of an open battery can cause skin irritation and/or chemical burns. Cobalt, cobalt compounds, nickel and nickel compounds can cause skin sensitization and an allergic contact dermatitis. Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

### Eye Contact:

Contents of an open battery can cause severe irritation and chemical burns. Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

## SECTION VII- PRECAUTIONS FOR SAFE HANDLING AND USE

### Storage:

Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life.

### Mechanical Containment:

Do not obstruct safety release vents on batteries. Encapsulation of batteries will not allow cell venting and can cause high-pressure rupture.

<b>Subject:</b>	Safety Data Sheet – Nickel Cadmium Battery				
<b>Document No:</b>	GYSUK 029	<b>Revision:</b>	B	<b>Date:</b>	7 <sup>th</sup> July 2020

**Handling:**

Accidental short circuit for a few seconds will not seriously affect the battery. However, this battery is capable of delivering very high short circuit currents. Prolonged short circuits will cause high cell temperatures which can cause skin burns. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, and metal covered tables or metal belts used for assembly of batteries into devices.

If soldering or welding to the battery is required, use of tabbed batteries is recommended.

Do not open battery. The negative electrode material may be pyrophoric. Should an individual cell from a battery become disassembled, spontaneous combustion of the negative electrode is possible. This is much more likely to happen if the electrode is removed from its metal container. There can be a delay between exposure to air and spontaneous combustion.

**Charging:**

This battery is made to be charged many times. Because it gradually loses its charge over a few months, it is good practice to charge battery before use. Use recommended charger. Improper charging can cause heat damage or even high pressure rupture. Observe proper charging polarity.

**SECTION VIII-ACCIDENTAL RELEASE OR SPILLAGE**

Steps to be taken in case material is released or spilled.

Batteries that are leaking should be handled with rubber gloves. Avoid direct contact with electrolyte. Wear protective clothing and a positive pressure Self-Contained Breathing Apparatus (SCBA).

**SECTION IX-SPECIAL PROTECTION INFORMATION****Ventilation Requirements:**

Not necessary under normal conditions.

**Respiratory Protection:**

Not necessary under normal conditions.

**Eye Protection:**

Not necessary under normal conditions. Wear safety glasses with side shields if handling an open or leaking battery.

**Gloves:**

Not necessary under normal conditions. Use neoprene or natural rubber gloves if handling an open or leaking battery.

<b>Subject:</b>	Safety Data Sheet – Nickel Cadmium Battery				
<b>Document No:</b>	GYSUK 029	<b>Revision:</b>	B	<b>Date:</b>	7 <sup>th</sup> July 2020

**Open Battery Storage:**

Battery should not be opened. Should a cell become disassembled, the electrode should be stored in a fireproof cabinet, away from combustibles.

**SECTION X - EXPOSURE CONTROLS / PERSON PROTECTION**

Occupational Exposure Limits: LTEP	NA	STEP	NA
Respiratory Protection (Specify Type)	NA		
Ventilation	Local Exhausts	NA	Special
	Mechanical (General)	NA	Other
Protective Gloves	NA	Eye Protection	NA
Other Protective Clothing or Equipment	NA		
Work / Hygienic Practices	NA		

**SECTION XI - ECOLOGICAL INFORMATION**

Not applicable.

**SECTION XII - DISPOSAL METHOD**

Dispose of the batteries in accordance with local and government legislation.

**SECTION XIII – TRANSPORTATION INFORMATION**

YBSUK hereby certify that the above captioned goods are non-dangerous and non-hazardous materials for air transport in any nature. The consignment is fully described by Proper Shipping Name and packed (short-circuit prevented), marked and in proper condition for carriage by sea.

**SECTION XIV – REGULATORY INFORMATION**

Special requirement in accordance local regulatory requirements.

<b>Subject:</b>	Safety Data Sheet – Nickel Cadmium Battery				
<b>Document No:</b>	GYSUK 029	<b>Revision:</b>	B	<b>Date:</b>	7 <sup>th</sup> July 2020

**SECTION XV – OTHER INFORMATION**

The data in this Safety Data Sheet relates only to the specific material designated herein.

**SECTION XVI – MEASURES FOR FIRE EXTINCTION**

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

END

**YBSUK reference document:**

JJJ/JS-QW751-06 (CDS 02 01 2019).